



in the coaming are standard. A number of options are available, such as the

removable dual seat for helmsman and passenger and moulded canopy. Fitted with twin

90 hp 4-stroke outboard engines, the test model raced across an offshore chop at 35 knots.



Visit our website at www.leisurecat.com.au for more information, photos and video clips.



# **General Specifications**

- LOA (including engines): 6.89 metres (22 ft 7 in)
- Moulded Length: 6.0 metres (19 ft 8 in)
- Beam: 2.55 metres (8 ft 4 in)
- Draught: 0.40 metre (1 ft 3 in)
- Fuel Storage: 300 litre (79 gal/US)
- Power (min. recom.): 2 x 70 hp Outboards.
- Aquaguard Gelcoat used in laminate.
- Fully-sealed, non-skid deck.
- Twin heavy-duty battery switches in console.
- Fibreglass lids with stays on storage area port and starboard.
- Open storage areas x 4 in coamings.
- Watertight hatches to moulded engine well areas.
- Fully moulded engine wells included in hulls.
- Full length wave breaker.
- Hull solid single-skin construction with reinforced frames and laminated transom to suit engine selection.
- Superstructure and cockpit deck moulding.
- Solid single-skin and sandwich (foam core) construction including localized reinforcing for deck hardware.
- Mould to incorporate walk-around cabin and twin front seat moulding.
- Rubber gunwale rub rail.
- Moulded console housing controls, electonics, radios.
- Storage under front bench seat (hinged top).
- FRP bulkheads (5) below deck forward collision bulkhead watertight.
- FRP footrests (2) to console.
- Windscreen in smoked acrylic with anodised frames.
- Foredeck sun-lounge with white UV cushion.
- S/s bow roller.
- S/s main deck bollard split with pin.
- S/s fuel deck filters (x2).
- S/s hand rail to console.
- S/s catches and hinges throughout.
- 4 x 100mm (4") cross bollards fitted.
- S/s recessed fuel tank breathers (x2).
- All under-floor compartments fitted with closed cell foam flotation as practicable.

## Mechanical/Electrical Features

- VHF Radio GME.
- Plumb fuel lines and fitted fuel/water filters.
- Binnacle station controls as supplied with engine package.
- Single station hydaulic outboard steering package with wheel.
- Two (2) 12 volt 2000gph electric bilge pumps fitted to motor well compartments with sure-bail float switches.
- Bilge lines to discharge overboard through non-return valves.
- Complete 12 volt electrical installation including all materials, switches, lights, tags, etc.
- Navigation lights and anchor light.
- BEP 6-gang DC splashproof switch fuse panel fitted at helm.
- Two (2) FRP fuel tanks 150 litres per side (total 300 litres) fitted with tank level senders.

# Cockpit/Deck Area Features

- Stainless steel bow rail.
- Hard-top with stainless steel frame.
- Removable Helm bench seating with UV cushion.
- Bolsters along inside of cockpit coaming.
- Marlin board extension with dive ladder.
- Stainless hand rails on swim platform.
- Fire extinguisher in moulded recess.
- Ritchie Explorer flush-mount compass.
- 406 Mhz EPIRB in moulded recess.
- Saltwater deck wash.

## **Optional Features**

- S/s rail around windscreen with rod holders.
- Soft-top with stainless steel frame.
- Freshwater supply.
- Swivel single seating on moulded base.
- · Carpeted deck.
- Live-bait tank fitted to rear coaming.
- Decals and stripes.
- S/s hinged dive ladder.
- S/s targa frame.

## All LeisureCats have a 4-year structural warranty on hull and deck

Note: LeisureCat/AussieCat Australia Pty Ltd strives continually to improve features and retains the right to alter any or all of these specifications without notice.



## **AUSTRALIA**

2 Egmont Road, Henderson Western Australia, 6166 Phone: +61-8-9437 6477 Fax: +61-8-9437 4877

Email: sales@leisurecat.com.au

#### MALAYSIA

41, Lorong Jala 14/KS 10, Teluk Gong 42000 Pelabuhan Klang, Kuala Lumpur, Malaysia

Phone: (603) 3134 1466 Fax: (603) 3134 1463

Email: sales@leisurecat.com.au